

CLAIM AMENDMENTS

A listing of an entire set of claims 1-13 is submitted herewith per 37 C.F.R. §1.121. This listing of claims 1-13 will replace all prior versions, and listings, of claims in the application.

1. (Currently Amended) A [[CSCT]] coherent-scatter computed tomography apparatus for examination of an object of interest, the [[CSCT]] coherent-scatter computed tomography apparatus comprising:

a source of radiation; and

a radiation detector array;

wherein the source of radiation is adapted to generate a fan-shaped radiation beam;

wherein the radiation detector array is asymmetrically arranged with respect to the fan-shaped radiation beam; and

wherein a first part of the radiation detector array is used for a cone beam data acquisition and a second part of the radiation detector array is used for scatter radiation measurements.

2. (Currently Amended) The [[CSCT]] coherent-scatter computed tomography apparatus of claim 1,

wherein the radiation beam penetrates the object of interest in a slice plane; and

wherein the radiation detector array is arranged such that the slice plane intersects the radiation detector array at a side thereof.

3. (Currently Amended) The [[CSCT]] coherent-scatter computed tomography apparatus of claim 2, wherein the object of interest is displaced with respect to the slice plane along a scanning direction which intersects the slice plane at an angle;

wherein a location where the slice plane intersects the radiation detector array is offset with respect to a geometrical center of the radiation detector array; and

wherein the location is offset from the geometrical center in the scanning direction.

4. (Currently Amended) The [[CSCT]] coherent-scatter computed tomography apparatus of claim 1,

wherein the radiation detector array comprises a plurality of detector lines; and

wherein the fan-shaped radiation beam has a width of at least two detector lines of the plurality of detector lines when [[it]] the radiation beam impinges onto the radiation detector array after transmission through the object of interest.

5. (Currently Amended) The [[CSCT]] coherent-scatter computed tomography apparatus of claim 4, wherein [[a]] only one first part of the radiation detector array is used for a cone beam data acquisition and [[a]] only one second part of the radiation detector is used for scatter radiation measurements.

6. (Currently Amended) The [[CSCT]] coherent-scatter computed tomography apparatus of claim 1,

wherein the source of radiation and the radiation detector array are rotatable around a rotational axis extending through an examination area for receiving the object of interest;

wherein the source of radiation is arranged opposite to the [[source of]] radiation detector array during scanning;

wherein the source of radiation generates a fan-shaped x-ray beam adapted to penetrate the object of interest in the examination area in a slice plane;

wherein the radiation detector includes a plurality of detector lines each with a plurality of detector elements arranged in a line;

wherein the plurality of detector lines are arranged parallel to the slice plane;

wherein a primary radiation attenuated by the object of interest impinges on a first line of the plurality of detector lines;

wherein the first line is not a second line of the plurality of detector lines; and

wherein the second line is extending close to the geometrical center of the radiation detector array.

7. (Currently Amended) The [[CSCT]] coherent-scatter computed tomography apparatus according to claim [[5]] 6, wherein the first line is arranged [[with]] at a distance from the [[first line]] geometrical center of the radiation detector array in a direction along which the object of interest is displaced with respect to the radiation detector array during scanning.
8. (Currently Amended) The [[CSCT]] coherent-scatter computed tomography apparatus of claim [[5]] 6,
wherein a third line of the plurality of detector lines measures a scatter radiation scattered from the object of interest; and
wherein the third detector line is offset from the first detector line in a direction along which the object of interest is displaced with respect to the radiation detector array during scanning.
9. (Currently Amended) The [[CSCT]] coherent-scatter computed tomography apparatus of claim [[5]] 6, wherein the first line is the last line of the radiation detector array in the direction along which the object of interest is displaced with respect to the radiation detector array.
10. (Currently Amended) Method of examining an object of interest, the method comprising:
[[the steps of]]
energizing a source of radiation such that it generates a fan-shaped radiation beam; and
measuring a primary radiation attenuated by the object of interest and a scatter radiation scattered by the object of interest by means of a radiation detector array which is asymmetrically arranged with respect to the fan-shaped radiation beam, wherein a first part of the radiation detector array is used for a cone beam data acquisition and a second part of the radiation detector array is used for scatter radiation measurements.
11. (Currently Amended) The method of claim 10,

wherein the radiation beam penetrates the object of interest in a slice plane;
wherein the radiation detector array is arranged such that the slice plane intersects the radiation detector array at a side thereof;
wherein the object of interest is displaced with respect to the slice plane along a scanning direction which intersects the slice plane at an angle;
wherein a location where the slice plane intersects the radiation detector array is offset with respect to a geometrical center line of the radiation detector array; and
wherein the location is in the scanning direction at a distance from the geometrical center line.

12. (Currently Amended) The method of claim 10,
wherein the radiation detector array comprises a plurality of detector lines; and
wherein the fan shaped radiation beam has a width of at least two detector lines of the plurality of detector lines when [[it] the radiation beam] impinges onto the radiation detector array after transmission through the object of interest such that [[a]] the first part of the radiation detector array is used for [[a]] the cone beam data acquisition and [[a]] the second part of the radiation detector is used for scatter radiation measurements.

13. (Currently Amended) [[Computer program]] A computer-readable medium tangibly embodying a program of instructions executable for operating a [[CSCT]] coherent-scatter computed tomography apparatus, wherein, when the [[computer program is]] instructions are executed on a processor of the [[CSCT]] coherent-scatter computed tomography apparatus, the [[computer program]] computer-readable medium causes the [[CSCT]] coherent-scatter computed tomography apparatus to perform the following [[operation]] operations:

energizing a source of radiation such that it generates a fan-shaped radiation beam; and
measuring a primary radiation attenuated by [[the] an] object of interest and a scatter radiation scattered by the object of interest by means of a radiation detector array which is asymmetrically arranged with respect to the fan-shaped radiation beam, wherein a first part of

the radiation detector array is used for a cone beam data acquisition and a second part of the radiation detector array is used for scatter radiation measurements.